



| REV. | DESCRIPTION | DRAWN | CHECKED | APPROVED |
|------|-------------|---------------|---------|----------|
| A | NEW RELEASE | YCH 08/17/07' | ~ | |
| | | | | |
| | | | | |

NOTES:

1.SPECIFICATION

- .CURRENT RATING: 5A Max.
- .DIELECTRIC WITH STANDING VOLTAGE: 500V(AC)
- .CONTACT RESISTANCE: 100mΩ Max.
- .INSULATION RESISTANCE: 1000MΩ(DC)Min.

2.PRODUCT NUMBER CODE:

DS1110-10 - X X X X

- SHELL SURFACE FINISHED
P1:SPRAY THE PAINT (GREEN)
- CONTACT PLATING
8: FULL GOLD FLASH
- COLOR OF HOUSING:
L: BLUE
- No. OF CONTACTS
19: 19pin

Tel: 86-574-63508787
Fax: 86-574-63510817

| | | | |
|-------------------|------------------|--|-------------------------|
| GENERAL TOLERANCE | ANGLE TOLERANCE | PROJECTION | TITLE |
| X. ±0.60 | X. ±5° | UNITS | MICRO JACK CONNECTOR |
| .X ±0.38 | .X ±3° | SHEET SIZE | SERIES DS1110-10 SERIES |
| .XX ±0.25 | .XX ±2° | | |
| DRAWING TYPE | CUSTOMER | 晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD | |
| SCALE | 1:1 SHEET 1 OF 1 | | |
| DRAWING NO. | C-DS1110-10-XXX | | |